SCI® Acoustic Underlayment

dBarrier™ Luxury Vinyl Underlayment

- Dampens sound and room noise in today's active environments
- Guardian™ antimicrobial inhibits the growth of mold, mildew, and odorcausing bacteria
- Smoothes out minor floor irregularities
- Installs quickly and easily
- For use over in-floor heating and is recommended by the RPA as an excellent choice
- Hypoallergenic and CRI Green Label Plus-certified

SPECIFICATIONS

Product Code: BV0340

Composition: Made of High-Density Synthetic Rubber

Density: $62 \text{ lbs/ft}^3 \text{ or } 42 \text{ oz/yd}^2$ Thickness: 0.056'' (1.42 mm)

R-Value: 0.02 Moisture Barrier: N/A* Color: Red

Castor Durability Test: Passes 25,000 Cycles**

Dimension: 54" x 44.44'

 $\begin{array}{lll} \text{Ft}^2/\text{Roll:} & 200 \\ \text{Yd}^2/\text{Roll:} & 22.22 \\ \text{Roll Weight:} & 58 \text{ lbs.} \end{array}$



ACOUSTICAL PROPERTIES

Impact Insulation 66 Class (IIC)***

ΔIIC 22
Sound Transmission 63
Class (STC)***

PROTECTION

Indoor Air Quality: CRI Green Label Plus-Certified

Antimicrobial: Yes
Warranty: Limited

*Separate moisture barrier should be used on slab foundation and below-grade installation

IIC: ASTM E492-09/ASTM E989-06 ΔIIC:AaSTM E2179-03

STC: ASTM E90/ASTM E413-10















For use under

- Luxury vinyl tile/plank
- Rigid composite
- Other premium resilient flooring
- Laminate
- Engineered wood
- Solid Hardwood





^{**}Passes Castor Durability Test for 25,000 cycles when tested under minimum of 3 mm double-glued luxury vinyl plank and minimum 3.2 mm floating-click

^{***}When tested with floor - ceiling assembly